

CHARGER SELECTION AND SPECIFICATION CHART

24V - 36V CHARGERS

Volts / Amps	Cabinet Size			Charger Rating / Selction Flooded Lead acid cells Wa Characteristics 80% Discharge Capacity (A/h's @ 5 hr rate)		
	Height	Width	Depth	8 Hr		12 Hr
24v15	280	425	275	84		120
24v20	280	425	275	112		160
24v25	310	500	300	140		200
24v30	310	500	300	168		240
24v40	310	500	300	224		320
24v50	310	500	300	280		400
24v60	310	500	300	336		480
24v80	800	500	400	448		640
24v100	800	500	400	560		800
24v120	800	500	400	672		960
24v140	800	500	400	784		1120
24v160	1000	400	500	896		1280
24v180	1000	400	500	1008		1440
24v200	1000	400	500	1120		1600
24v220	1000	400	500	1232		1760
24v240	1000	400	500	1344		1920
36v15	280	425	275	84		120
36v20	310	500	300	112		160
36v25	310	500	300	140		200
36v30	310	500	300	168		240
36v40	310	500	300	224		320
36v50	310	500	300	280		400
36v60	800	500	400	336		480
36v70	800	500	400	392		560
36v80	800	500	400	448		640
36v100	800	500	400	560		800
36v120	1000	400	500	672		960
36v140	1000	400	500	784		1120
36v160	1000	400	500	896		1280
36v180	1000	400	500	1008		1440
36v200	1000	400	500	1120		1600

For further information contact:

www.forklift-batteries.co.uk