

CHARGER SELECTION AND SPECIFICATION CHART

24V - 36V CHARGERS

| Volts / Amps | Cabinet Size | | | Charger Rating / Selction Flooded Lead acid cells Wa Characteristics 80% Discharge Capacity (A/h's @ 5 hr rate) | | |
|--------------|--------------|-------|-------|---|--|-------|
| | Height | Width | Depth | 8 Hr | | 12 Hr |
| | | | | | | |
| 24v15 | 280 | 425 | 275 | 84 | | 120 |
| 24v20 | 280 | 425 | 275 | 112 | | 160 |
| | | | | | | |
| 24v25 | 310 | 500 | 300 | 140 | | 200 |
| 24v30 | 310 | 500 | 300 | 168 | | 240 |
| 24v40 | 310 | 500 | 300 | 224 | | 320 |
| 24v50 | 310 | 500 | 300 | 280 | | 400 |
| 24v60 | 310 | 500 | 300 | 336 | | 480 |
| | | | | | | |
| 24v80 | 800 | 500 | 400 | 448 | | 640 |
| 24v100 | 800 | 500 | 400 | 560 | | 800 |
| 24v120 | 800 | 500 | 400 | 672 | | 960 |
| 24v140 | 800 | 500 | 400 | 784 | | 1120 |
| | | | | | | |
| 24v160 | 1000 | 400 | 500 | 896 | | 1280 |
| 24v180 | 1000 | 400 | 500 | 1008 | | 1440 |
| 24v200 | 1000 | 400 | 500 | 1120 | | 1600 |
| 24v220 | 1000 | 400 | 500 | 1232 | | 1760 |
| 24v240 | 1000 | 400 | 500 | 1344 | | 1920 |
| | | | | | | |
| 36v15 | 280 | 425 | 275 | 84 | | 120 |
| | | | | | | |
| 36v20 | 310 | 500 | 300 | 112 | | 160 |
| 36v25 | 310 | 500 | 300 | 140 | | 200 |
| 36v30 | 310 | 500 | 300 | 168 | | 240 |
| 36v40 | 310 | 500 | 300 | 224 | | 320 |
| 36v50 | 310 | 500 | 300 | 280 | | 400 |
| | | | | | | |
| 36v60 | 800 | 500 | 400 | 336 | | 480 |
| 36v70 | 800 | 500 | 400 | 392 | | 560 |
| 36v80 | 800 | 500 | 400 | 448 | | 640 |
| 36v100 | 800 | 500 | 400 | 560 | | 800 |
| | | | | | | |
| 36v120 | 1000 | 400 | 500 | 672 | | 960 |
| 36v140 | 1000 | 400 | 500 | 784 | | 1120 |
| 36v160 | 1000 | 400 | 500 | 896 | | 1280 |
| 36v180 | 1000 | 400 | 500 | 1008 | | 1440 |
| 36v200 | 1000 | 400 | 500 | 1120 | | 1600 |
| | | | | | | |

For further information contact:

www.forklift-batteries.co.uk