

CHARGER SELECTION AND SPECIFICATION CHART

48V - 72V - 80V CHARGERS

Volts / Amps	Cabinet Size			Charger Rating / Selction Flooded Lead acid cells Wa Characteristics 80% Discharge Capacity (A/h's @ 5 hr rate)		
	Height	Width	Depth	8 Hr		12 Hr
48v50	800	500	400	280		400
48v60	800	500	400	336		480
48v70	800	500	400	392		560
48v80	800	500	400	448		640
48v90	800	500	400	504		720
48v100	800	500	400	560		800
48v120	1000	400	500	672		960
48v140	1000	400	500	784		1120
48v160	1000	400	500	896		1280
48v180	1000	400	500	1008		1440
48v200	1100	600	500	1120		1600
72v60	800	500	400	336		480
72v70	800	500	400	392		560
72v80	800	500	400	448		640
72v90	1000	400	500	504		720
72v100	1000	400	500	560		800
72v120	1000	400	500	672		960
72v140	1100	600	500	784		1120
72v160	1100	600	500	896		1280
72v180	1100	600	500	1008		1440
72v200	1100	600	500	1120		1600
80v60	800	500	400	336		480
80v70	800	500	400	392		560
80v80	800	500	400	448		640
80v90	800	500	400	504		720
80v100	1000	400	500	560		800
80v120	1000	400	500	672		960
80v140	1100	600	500	784		1120
80v160	1100	600	500	896		1280
80v180	1200	700	550	1008		1440
80v200	1200	700	550	1120		1600

For further information contact:

www.forklift-batteries.co.uk