

## Selection Table Single Phase (Green 2 and 4)

PRODUCT CODE	VOLTAGE	OUTPUT	MAINS (VAC)	INPUT CURRENT	8HR RECHARGE	12HR RECHARGE	DIMENSIONS	WEIGHT
24V50-01-SP	24	50	230	7.5	280-340	450-550	300x475x180	11
24V60-01-SP		60	230	9	340-410	540-660	300x475x180	11
24V70-01-SP		70	230	10.5	390-480	630-770	300x475x180	11
24V80-01-SP		80	230	12	450-550	720-880	333x520x180	13
24V90-01-SP		90	230	13.5	510-620	810-990	333x520x180	13
24V100-01-SP		100	230	15	560-690	900-1100	333x520x180	13
24V120-01-SP		120	230	18	680-830	1080-1320	333x520x180	13
36V40-01-SP	36	40	230	9	230-280	360-440	300x475x180	11
36V45-01-SP		45	230	10	250-310	410-550	300x475x180	11
36V50-01-SP		50	230	11	280-340	450-550	333x520x180	13
36V60-01-SP		60	230	13.5	340-410	540-660	333x520x180	13
36V70-01-SP		70	230	15.5	390-480	630-770	333x520x180	13
36V80-01-SP		80	230	18	450-550	720-880	333x520x180	13
36V90-01-SP		90	230	20	510-620	810-990	333x520x180	13
48V30-01-SP	48	30	230	9	170-210	270-330	300x475x180	11
48V40-01-SP		40	230	12	230-280	360-440	300x475x180	11
48V50-01-SP		50	230	15	280-340	450-550	333x520x180	13
48V60-01-SP		60	230	18	340-410	540-660	333x520x180	13
48V75-01-SP		75	230	22.5	420-520	680-830	333x520x180	13
72V25-01-SP	72	25	230	11	140-170	230-280	300x475x180	11
72V30-01-SP		30	230	13.5	170-210	270-330	333x520x180	13
72V40-01-SP		40	230	18	230-280	360-440	333x520x180	13
72V50-01-SP		50	230	22.5	280-340	450-550	333x520x180	13
80V20-01-SP	80	20	230	10	110-140	180-220	300x475x180	11
80V30-01-SP		30	230	15	170-210	270-330	333x520x180	13
80V40-01-SP		40	230	20	230-280	360-440	333x520x180	13