

CEMB SELECTION TABLE - SINGLE PHASE

Type	Output Voltage (V)	Output Current	Mains (VAC)	Input current (A)	Dimensions	Charging time/ battery capacity (Ah max.)		
						8hrs	10hrs	12hrs
24v20a-01-PG	24	20	240	3	L280 W330 H200	-	110	140
24v25a-01-PG		25	240	4	L280 W330 H200	-	150	175
24v30a-01-PG		30	240	5	L280 W430 H300	-	180	210
24v40a-01-PG		40	240	6	L280 W430 H300	-	220	280
24v50a-01-PG		50	240	8	L280 W430 H300	-	300	340
24v60a-01-PG		60	240	9	L280 W430 H300	-	350	400
36v15a-01-PG	36	15	240	4	L280 W330 H200	-	90	105
36v20a-01-PG		20	240	5	L280 W430 H300	-	110	140
36v25a-01-PG		25	240	6	L280 W430 H300	-	150	175
36v30a-01-PG		30	240	7	L280 W430 H300	-	180	210
36v40a-01-PG		40	240	9	L280 W430 H300	-	220	280

REVOLUTION SELECTION TABLE - SINGLE PHASE

Type	Type	Output Current	Mains (VAC)	Input current (A)	Dimensions	Charging time/ battery capacity (Ah max.)		
						8hrs	10hrs	12hrs
24v60a-01-PG	24	60A	240	9	L580 W365 H450	330	350	400
24v80a-01-PG		80A	240	13	L580 W365 H450	440	480	550
24v100a-01-PG		100A	240	16	L580 W365 H450	550	610	680
24v120a-01-PG		120A	240	19	L580 W365 H450	660	750	800
36v60a-01-PG	36	60A	240	16	L580 W365 H450	330	360	390
36v80a-01-PG		80A	240	25	L580 W365 H450	440	480	520
36v100a-01-PG		100A	240	32	L580 W365 H450	550	600	650
48v60a-01-PG	48	60A	240	19	L580 W365 H450	330	350	400
48v80a-01-PG		80A	240	25	L580 W365 H450	440	480	550
48v100a-01-PG		100A	240	31	L580 W365 H450	550	610	680
72v60a-01-PG	72	60A	240	28	L580 W365 H450	330	350	400
72v80a-01-PG		80A	240	38	L580 W365 H450	440	480	550
80v60a-01-PG	80	60A	240	31	L580 W365 H450	330	350	400
80v80a-01-PG		80A	240	42	L580 W365 H450	440	480	550

APPLICATIONS: FORKLIFTS | CLEANING MACHINES | ACCESS PLATFORMS | ELECTRIC TOW TRACTORS | ELECTRIC VEHICLES