

GOT was formed by a group of engineers with decades of experience in the design and construction of charge and discharge systems. The company focuses its resources on the development and construction of new chargers and discharge machines.

Based in San Marino the company serves the world market as a leader of innovation and quality.

Easy Single Phase

Main features:
 Power up to 2.5 kW, from 24V up to 96V,
 from 17A up to 70A
 Programmable via USB
 type A/B port or via display
 Graphical display



Revolution Single Phase

Main features:
 Modular system (3 configurable modules)
 Power up to 8 kW, up to 150A @ 48V,
 up to 100A @ 80V, up to 75A @ 96V
 Programmable via USB
 type A/B port or via display
 Graphical display



Easy Three Phase

Main features:
 Power up to 4.5 kW, from 24V up to 96V,
 from 25A up to 120A
 Programmable via USB type A/B port or via
 display Graphical display



Revolution Three Phase

Main features:
 Modular system (5-6 configurable modules)
 Power up to 16 kW, 300A @ 48 V,
 up to 200A @ 80 V, up to 150A @ 96V
 Programmable via USB
 type A/B port or via display
 Graphical display.



Selection Table Easy & Revolution Single Phase

Type	Output Voltage (V)	Output Current	Mains (VAC)	Input current (A)	Dimensions L x Wx H	Charging time/ battery capacity (Ah max.)	
						10hrs	12hrs
24V20A-01-REV	24V	20	240	3	280X330X200	100	120
24V25A-01-REV		25	240	4	280X330X200	125	150
24V30A-01-REV		30	240	5	280X330X300	155	185
24V40A-01-REV		40	240	6	280X330X300	195	250
24V50A-01-REV		50	240	8	280X330X300	260	310
24V60A-01-REV		60	240	9	280X330X300	320	370
24V80A-01-REV		80	240	13	470X465X700	390	500
24V100A-01-REV		100	240	16	470X465X700	510	620
24V120A-01-REV		120	240	19	470X465X870	625	720
24V140A-01-REV		140	240	22	470X465X870	750	875
24V160A-01-REV		160	240	25	470X465X870	850	960
36V20A-01-REV	36V	20	240	5	280X430X300	100	120
36V30A-01-REV		30	240	7	280X430X300	155	185
36V40A-01-REV		40	240	9	280X430X300	195	250
36V60A-01-REV		60	240	16	470X465X700	320	380
36V80A-01-REV		80	240	19	470X465X700	390	500
36V100A-01-REV		100	240	25	470X465X700	510	620
36V120A-01-REV		120	240	29	470X465X870	625	720
36V140A-01-REV		140	240	35	470X465X870	750	875
36V160A-01-REV		160	240	39	470X465X870	850	960
48V20A-01-REV	48V	20	240	8	280X430X300	100	120
48V30A-01-REV		30	240	10	280X430X300	155	185
48V40A-01-REV		40	240	13	280X430X300	195	250
48V60A-01-REV*		60	240	19	470X465X700	320	380
48V80A-01-REV*		80	240	25	470X465X700	390	500
48V100A-01-REV*		100	240	31	470X465X700	510	620
48V120A-01-REV*		120	240	38	470X465X870	625	720
48V140A-01-REV		140	240	45	470X465X870	750	875
48V160A-01-REV		160	240	51	470X465X870	850	960
72V60A-01-REV	72V	60	240	28	470X465X700	320	380
72V80A-01-REV		80	240	38	470X465X700	390	500
72V100A-01-REV		100	240	48	470X465X870	510	620
72V120A-01-REV		120	240	56	470X465X870	625	720
72V140A-01-REV		140	240	67	470X465X870	750	875
80V60A-01-REV	80V	60	240	31	470X465X700	320	380
80V80A-01-REV		80	240	42	470X465X700	390	500
80V100A-01-REV*		100	240	52	470X465X870	510	620
80V120A-01-REV*		120	240	63	470X465X870	625	720
80V140A-01-REV		140	240	73	470X465X870	750	875

*Designates Easy Charger range options.

Selection Table Easy & Revolution Three Phase

Type	Output Voltage (V)	Output Current	Mains (VAC)	Input current (A)	Dimensions L x Wx H	Charging time/ battery capacity (Ah max.)	
						10hrs	12hrs
24V60A-03-REV	24V	60	440	4	470X465X700	320	380
24V80A-03-REV		80	440	5	470X465X700	390	500
24V100A-03-REV		100	440	6	470X465X700	510	620
24V120A-03-REV		120	440	7	470X465X870	625	720
24V140A-03-REV		140	440	9	470X465X870	750	875
24V160A-03-REV		160	440	10	470X465X870	850	960
36V60A-03-REV	36V	60	440	5	470X465X700	320	380
36V80A-03-REV		80	440	7	470X465X700	390	500
36V100A-03-REV		100	440	9	470X465X700	510	620
36V120A-03-REV		120	440	11	470X465X700	625	720
36V140A-03-REV		140	440	13	470X465X700	750	875
36V160A-03-REV		160	440	14	470X465X870	850	960
48V40A-03-REV	48V	40	440	5	500X360X450		240
48V60A-03-REV		60	440	7	470X465X700	320	380
48V80A-03-REV*		80	440	10	470X465X700	390	500
48V100A-03-REV*		100	440	12	470X465X700	510	620
48V120A-03-REV*		120	440	14	470X465X870	625	720
48V140A-03-REV		140	440	16	470X465X870	750	875
48V160A-03-REV		160	440	18	470X465X870	850	960
72V40A-03-REV	72V	40	440	6	500X360X450		240
72V60A-03-REV		60	440	11	470X465X700	320	380
72V80A-03-REV		80	440	14	470X465X700	390	500
72V100A-03-REV		100	440	16	470X465X870	510	620
72V120A-03-REV		120	440	18	470X465X870	625	720
72V140A-03-REV		140	440	21	470X465X870	750	875
72V160A-03-REV		160	440	23	565X500X960	850	960
80V40A-03-REV	80V	40	440	8	500X360X450		240
80V60A-03-REV		60	440	12	470X465X700	320	380
80V80A-03-REV		80	440	16	470X465X870	390	500
80V100A-03-REV*		100	440	18	470X465X870	510	620
80V120A-03-REV*		120	440	21	470X465X870	625	720
80V140A-03-REV		140	440	24	565X500X960	750	875

*Designates Easy Charger range options.